P2.02 SCALE: 1/4" = 1'-0"

GENERAL NOTES:

- A. VERIFY ALL EXISTING CONDITIONS RELATIVE TO THE SCOPE OF WORK. DO NOT FABRICATE W/O CONFIRMING SPACE EXISTS, FOR SIZES REQUIRED.
- B. COORDINATE ALL PLUMBING WORK WITH GENERAL CONTRACTOR, CONTROL CONTRACTOR, ELECTRICAL AND ARCHITECTURAL.
- C. ROUTE BUILDING SEWER WITH 2% SLOPE.
- D. PROVIDE ACCESSIBLE WATER HAMMER ARRESTOR ON EACH FLUSH VALVE SUPPLY LINE.
- E. PROVIDE 2 INCH MINIMUM WASTE LINE FOR UNDERGROUND INSTALLATIONS.
- F. PROVIDE ACCESSIBLE WATER HAMMER ARRESTORS ON EACH FLUSH VALVE SUPPLY LINE.

- 3. NEW CLINIC DOMESTIC COLD & HOT WATER
- 5. PROVIDE THERMOSTATIC MIXING VALVE AT PUBLIC
- 6. RAIN DRAIN DOWN TO UNDERGROUND. PROVIDE
- MATCH EXISTING. PROVIDE 2% SLOPE ON HORIZONTAL RUNS. SEE DETAIL 6/P6.01. 7. MEDICAL GASES AND EQUIPMENT BY OTHERS. SEE
- REQUIREMENTS OF 02 N20 MA AND VACUUM PIPING, DENTAL SINKS, STERILIZERS, VACUUM PUMP AND COMPRESSORS.
- 8. ROUTE COLD, HOT WATER AND HOT WATER RECIRCULATION PIPING ABOVE THE CEILING.
- PROVIDE HOT WATER RECIRCULATION ZONE BALANCING VALVE AND SHUT-OFF VALVE.

PLUMBING KEY NOTES:

1. 2"WASTE FOR FUTURE SINK. TERMINATE AT WALL

2. UNDERCOUNTER SOLIDS INTERCEPTOR, SEE DETAIL 8/P6.01.

SUPPLY. PROVIDE ACCESSIBLE SHUT-OFF VALVE. 4. VENT UP TO ROOF.

LAVATORY.

DOWNSPOUT BOOTH AND GRADE CLEAN-OUT TO

BURKHART DENTAL DRAWINGS FOR DESIGN

10. EXISTING HOT WATER RECIRC BALANCE VALVE.

REBALANCE WATER FLOW PER SCHEDULE.

10

REVISIONS: 1 MISC REV.

FLOOR PLAN -PLUMBING

